



www.masabainc.com

Feeders

Portable 10'x16' Hydraulic Grizzly Feeder Hopper

Main Frame and Chassis

- Tandem Axle Chassis
- Total Weight: **58,400 lbs**
- Walking Beam steel frame
- Heavy Duty Suspension
- (8) 11R x 22.5 radial tires
- Brakes
- Lights
- (2) Crank Down Landing Jacks
 - Manual Pin Lock
- Mudflaps

48" x 48' Adjustable Height Discharge Conveyor

- Hydraulic Raise and Lower
- **40 hp**
- CEMA C Idlers
- Impact Idlers
- Head Drive
- Dodge TA6 Gear Reducer
- Class II Drives
- 3 Ply Belting with Mechanical Splice
- Belt Scraper

42" x 20' Belt Feeder

- **40 hp**
- Adjustable Belt Speed
- Head Drive
- Dodge TA6 Gear Reducer
- CEMA C Idlers
- 3 Ply Belting with Mechanical Splice
- Belt Scraper

Features

- (1) Coat 2 part Urethane Primer
- (1) Coat 2 part Urethane Paint
- Steel-shot blasted
- (2) Owner's manual for start-up and maintenance

Hopper

- Dimensions: **16' x 10'**
- Volume: **14.25 cubic yards**
- 1/4" Steel Plate Baffle
- Lined with weld-in 3/8" AR400
- Reversible Grizzly Top
 - Tilts to Either Side
 - (2 sets) Self-Relieving Grizzly Bars with Optional 6" or 8" spacing
 - **15 hp** hydraulic package
- (2) Hopper Side Guards
 - Rubber
- (2) Hinged Bulkheads

Options



- Switchgear
 - NEMA 4 Enclosure
- Hydraulic Lifting Jacks and Power Unit
- 12V Conveyor Power Raise Control
- Intraflo Autolube System
- Vulcanized Belt Splice

STRENGTH
YOU
CAN **DEPEND** On!

MASABA Portable 10' x 16' Hydraulic Grizzly Feeder

BENEFITS OF MASABA

Our hoppers and feeders are engineered to be the most rugged and durable on the market. Built from 1/4" steel, our hoppers (1) are built to handle the roughest conditions. The Belt Feeder (2) will ensure a constant flow of material to the rest of your operation. This combination is mounted on a heavy-duty Walking Beam Frame (3) built with the same strength and toughness you expect from all Masaba equipment. Your Masaba Feeder is designed to be easily compatible with the rest of your operation.



Travel Dimensions

67' 8" l x 12'-1 3/8" w x 14'-3 15/16" h

Operating Dimensions

67' 8" l x 12' 1 3/8" w x 19' h

Weight

Kingpin: 25,600 lbs

Axle: 32,800 lbs

NOTE: Listed weights are not exact. Actual weights will vary based on screen size, brand, options, etc.



Adjustable Discharge Conveyor



Hydraulic Grizzly Bars



42" Belt Feeder

MASABA

MASABAinc.com
1-877-627-2220
info@MASABAinc.com

REVISION December 2013

NOTE: SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE: Because MASABA, Inc. may use in its catalog & literature, field photographs of its products which may have been modified by the owners, products furnished by MASABA, Inc. may not necessarily be as illustrated therein. Also continuous design progress makes it necessary that specifications be subject to change without notice. All sales of the products of MASABA, Inc. are subject to the provisions of its standard warranty. MASABA, Inc. does not warrant or represent that its products meet any federal, state, or local statutes, codes, ordinances, rules, standards or other regulations, including OSHA and MSHA, covering safety pollution, electrical, wiring, etc. Compliance with these statutes and regulations is the responsibility of the user and will be dependent upon the area and the use to which the product is put by the user. In some photographs, guards may have been removed for illustrative purposes only. This equipment should not be operated without all guards attached in their normal position. Placement of guards and other safety equipment is often dependent upon the area and the use to which the product is put. A safety study should be made by the user of the application, and, if required, additional guards, warning signs and other safety devices should be installed by the user, wherever appropriate before operating the products.